

INSULATION

Pipe Insulation (6' Lengths) Wall Thickness (\$/ft) Pipe Size



Pre-Slit & Pre-Glued

Max Temp 200F°(93°C)

Flexible to -100°F (-73°C)


ID Size	1/2" R		3/4" R		IPS - Copper
	\$	R	\$	R	
5/8"	.73	3.3	1.16	5.3	* - 1/2
7/8"	.82	3.0	1.39	4.8	1/2 - 3/4
1 1/8"	.95	2.9	1.83	4.6	3/4 - 1
1 3/8"	1.31	2.8	2.40	4.4	1 - 1 1/4
1 5/8"	1.60	2.7	3.39	4.2	1 1/4 - 1 1/2
2"	1.79	2.6	3.82	4.0	1 1/2 - *
2 1/8"	2.10	2.6	4.36	4.0	* - 2
2 3/8"	2.36	2.6	4.83	4.0	2 - *
2 5/8"	2.67	2.6	5.52	3.9	* - 2 1/2
2 7/8"	3.30	2.6	6.32	3.9	2 1/2 - *

PHYSICAL PROPERTIES


Maximum Service Temperature °F (°C)	200 (93)	ASTM C 1427
Minimum Service Temperature °F (°C) ①	-297 (-183)	ASTM C 1427
Water Vapor Permeability, Perm-In	0.02	ASTM E 96, Procedure A
Water Absorption, % by Volume	0.2	ASTM C 1763
Chemical/Solvent Resistance	Good	
Mildew Resistance/Air Erosion	Pass	
Flame Spread and Smoke Developed Index through 1" (25 mm) thickness	25/50 rated	ASTM E 84

Outdoor Use

Painting with WB Finish or other protective jacketing is required to prevent damage to the insulation in exterior applications and to comply with the insulation protection sections of the International Energy Conservation Code (IECC) and ASHRAE 90.1.



#396
 Cover Kit
 Flexible P-Trap Cover Rotation
 and Coil-Fit Valve/Supply Cover



FLEX-WRAP Closed cell polyethylene pipe wrap	3/32" x 6" x 200'	\$ 16.50
COVER KIT P-trap & Angle Stops/Risers	#396	62.50
FIBERGLASS DUCT WRAP	1 1/4" x 9" x 150'	78.50
HANDI-CAP-WRAP *	1/8" x 2" x 40'	29.00

* Pressure sensitive adhesive backing