

# CLAMPS



**LOX-ON**

All Stainless ( $\frac{9}{16}$ " Band) *Clamp Size*  
*Pipe Size* *Min - Max*

6806	\$ 1.31	1/2"	3/8" - 7/8"
6808	"	1/2"	7/16" - 1"
6810	"	1/2", 3/4"	1/2" - 1 1/8"
6812	1.32	1/2", 3/4"	1/2" - 1 1/4"
6816	"	3/4", 1"	3/4" - 1 1/2"
6820	1.35	1", 1 1/4"	3/4" - 1 3/4"
6824	"	1 1/4", 1 1/2"	1" - 2"
6828	1.36	1 1/2"	1 5/16" - 2 1/4"
6832	"	2"	1 9/16" - 2 1/2"
6836	1.43	-	1 7/8" - 2 3/4"
6840	1.57	2", 2 1/2"	1 1/8" - 3"
6844	1.82	-	1 5/16" - 3 1/4"
6848	"	-	1 5/8" - 3 1/2"
6852	1.90	3"	1 7/8" - 3 3/4"
6856	"	-	2 1/8" - 4"
6864	2.10	-	2 5/8" - 4 1/2"
6872	2.20	4"	3 1/8" - 5"
6880	2.28	-	3 5/8" - 5 1/2"
6888	2.45	-	4 1/4" - 6"
6896	2.68	-	4 3/4" - 6 1/2"
68104	2.69	6"	4" - 7"



*Clamp Size*  
*Min - Max*

6932	\$ 2.35	1 1/16" - 2 5/8"
------	---------	------------------

## POW'R-GEAR

All Stainless ( $\frac{5}{8}$ " Band) *Min - Max*

6L175	\$ 3.58	1" - 1 3/4"
6L200	3.75	1 1/4" - 2 1/8"
6L250	3.85	1 3/4" - 2 5/8"



## MICRO-GEAR

Part Stainless ( $\frac{5}{16}$ " Band) *Min - Max*

6202	\$ 1.13	1/4" - 5/8"
6203	1.13	5/16" - 7/8"

## Marine Grade Clamp


All Parts 300 Stainless *Min - Max*

6312	\$ 1.59	1/2" - 1 1/4"
6316	1.59	3/4" - 1 1/2"
6324	1.62	1" - 2"
63176	5.80	2 1/2" - 11 1/2"
63248	6.75	2 1/2" - 16"



**Torque Ratchet  
 Wrench 60#**

**\$ 35.00**



**Plastic PipeCutter**

1/8" - 1 1/2" od

**\$ 68.00**

Blades **24.50**



**EZ-1**


1/8" - 1 1/4" od

**\$ 9.95**

Blades **4.95**

### How To Clamp Polyethylene Pipe

Placing the clamp over the serrations of the fittings assures a tight joint and eliminates the possibility of seepage. When double clamping, set screws on clamps 90 degrees apart.



Right



Wrong

Clamps - W, boxes - X  
 Tools - V